

**Main Office:** 1135 Lance Road, Norfolk, Virginia 23502  
Quality Equipment and Service Since 1962

Telephone: 757-461-0077  
Telefax: 757-461-0808  
Telephone: 704-374-0600  
Telefax: 704-374-1008

**Branch Office:**  
4715 Stockholm Court, Charlotte, NC 28273

**Small Compressor System for Fueling Vehicles with Natural Gas (CNG):  
5 to 50 HP, Air Cooled Design**



<b>MODEL: *</b> (HP = motor Horse Power)	<b>UR40 - (HP) *</b>	<b>UR50 - (HP) *</b>	<b>UR65 - (HP) *</b>
Manufacturer:	<b>Universal Air Products GPD</b>		
Power (Electric Motor):*	5 to 20 HP*	10 to 30 HP*	15 to 50 HP*
Inlet Pressure:	1 inch WC or higher	1 inch WC or higher	1 inch WC or higher
Discharge Pressure:	6000 psig maximum		
Flow (subject to inlet /outlet):	5 to 25 SCFM	10 to 35 SCFM	20 to 80 SCFM
Vehicles fueled / day:	Consult sales representative		
Compression Stages:	4	4	4
Cooling System Design:	Air	Air	Air
Electrical Classification (USA)	NEC NEMA Design 7, Class 1, Division 2, Group C, D		
Electrical Voltage / Hz	200 to 575V (50 or 60 Hz)		
Electrical Phase (Ph)	1 Ph to 10HP; 3 Ph all HP	1 Ph to 10HP; 3 Ph all HP	3 Ph

(Continued on next page)

**\*Larger HP Systems Available**

**Additional NG Compression System Features Include:**

- Structural steel base frame, fork-liftable
- PLC (programmable logic control)
- Digital message board with fault history and real time readings for all sensors
- Common fault indicator light for programmed shutdown conditions
- Full voltage motor starter and electrical control system mounted and wired
- Control voltage circuit with step-down transformer
- Motor overloads
- Power-on light
- Emergency kill (mushroom) switch
- On-off switch for start/stop control (two-way switch)
- Face gauge panel, including 1<sup>st</sup> stage thru final discharge pressure and oil pressure.
- Face gauge for final system pressure prior to the pressure maintaining valve
- Discharge pressure sensor with infinite setting control and multiple set points
- Low and high inlet pressure sensor
- Low oil pressure sensor
- High outlet temperature sensor (1<sup>st</sup> & 4<sup>th</sup> stages)
- Contacts provided for remote monitoring of system controls
- Built-in air cooled intercoolers and aftercooler
- Moisture separation, all stages
- Auto condensate drainage, all stages
- Cartridge dryer / filtration manifold, installed
- Forced lubrication system with oil pump and filter
- Crankcase breather piped to inlet or vent (subject to inlet conditions)
- Automatic compressor unloading system with vented to vapor recovery tank
- Non-return valve at discharge
- Minimum pressure valve at discharge
- Finish paint in blue or light gray enamel
- ASME, inlet gas surge tank with pressure gauge and gas tight relief valve
- Integrated vapor recovery system with ASME storage vessel regulated to system inlet
- Detailed general arrangement, electrical and flow diagrams for customer review and approval prior to system construction
- Detailed operations, maintenance and parts manuals provided in electronic or hard copy format (Standard English, alternate languages available at option)

**Typical Feature/Options Available:**

- Completely custom designs
  - Larger horse power ( kW)
  - Water cooled compressor or aftercooler designs
  - NEMA 7, Class 1, Division 1; rather than Division 2
  - Loose starter and/or electrical controls for mounting remotely at the job site
  - Reduced voltage starter (wye-delta, solid state or VFD)
  - Wired / wireless (LAN and/or WAN) based controls with monitoring capabilities (HMI and/or SCADA)
  - Combination style disconnect switch for the motor starter
  - Full system enclosures for sound reduction, safety or ambient protection
- (Continued on next page)**

- Off-shore base frame (skid) design with lifting eye and drag provisions
- Low ambient protection
- Inlet pressure regulation
- Outlet pressure regulation
- Vapor recovery tank pressure or temperature sensors
- Analog controls rather than PLC
- Custom programming of the PLC:
  - Duplex or triplex system control design & programming
  - Remote monitoring or controlling of the system
  - Customer site specific control or maintenance features
  - Remote operation, monitoring and diagnostics
- Engine driven designs
- High pressure storage tanks (ASME or DOT)
- Priority fill to high pressure gas storage
- Cascade fill to the vehicle gas storage
- Gas dispensing systems
- Custom inlet or discharge gas dryer in lieu of standard cartridge dryer manifold
- Inlet or discharge gas filtration
- Finish paint in epoxy and/or customer's color selection
- Hot dip galvanized structural steel base frame
- System modifications for non-municipal fuel gases, including biogas, landfill, digester, wastewater, Hydrogen and synthetic-gases. (Typical gas analysis required)
- Installation & startup
- Aftermarket technical support or site services
- Manuals provided in languages other than English

**END**