

Oil Free Screw Compressors

EnviroAire T/TVS 90 - 160 Series Fixed & Variable Speed







When PureAir Technology is High Priority

There's a lot riding on the quality of your air. The presence of particles, condensate, oil and oil vapour in a compressed air system can lead to downtime, product spoilage and recall, damage to your brand reputation, or worse, harmed consumers and product liability. Eliminate these risks with the oil-free T/TVS Series.

For lower cost of ownership

Oil-free systems deliver lower operational and maintenance costs over a system's life, while still maintaining the highest quality of compressed air.

For reliability

A robust product and system design delivers top quality air, protecting sensitive downstream equipment, lowering maintenance and extending equipment life.

ISO 8573 Class 0 Oil-Free Air

Class 0 is the most stringent air class defined by ISO 8573, part 1. Our oilfree compressors are certified Class 0 for no oil content by TUV to ensure your air quality exceeds specifications.

For productivity

The use of an oil-free Class 0 certified compressor guarantees contamination-free air, eliminating the risk of product spoilage and waste.

For serviceability

Our oil-free equipment is designed specifically to make maintenance easy by providing clear access to consumable components.

ISO 8573-1 Air Quality Classes						
Quality Class	Oil & Oil Vapor mg/m³					
0	< 0.01					
1	0.01					
2	0.1					
3	1					
4	5					

Gardner Denver – The Compressed Air system provider you can trust















Analysis Consulting

Project Installation planning

Assure Service & Warranty Maintenance Original spare parts

Il iConn remote rts monitoring



What makes our oil-free EnviroAire T/TVS90-160 screw compressors unique?

State-of-the-Art Airend Up to **8%** higher flow compared to industry standard

Dedicated 7.5, 8.5 and 10.5 bar models

Up to 7% (Fixed Speed) & 5%
(Variable Speed) energy reduction

 Variable speed models with turndown rates of up to 71%



The Airend - How we build reliability into every detail

Compressor rotors take a beating. Over time, their surfaces can deteriorate, leading to reduced air flow and increasing risk of corrosion.

Gardner Denver eliminates this problem with UltraCoat, an advanced rotor and housing protection process that ensures the most durable coating, with unmatched adhesion properties and temperature resistance.

In conjunction with a second-stage stainless steel rotor, UltraCoat delivers greater reliability in performance and air quality, rotor longevity, increased uptime, and reduced energy costs.

The optimised 2-stage airend design is a maintenance-free, sealed drive system which enhances reliability and improves efficiency.

At a glance

- Class Zero Oil FREE RotaryScrew Compressors
- Air- and Water-Cooled
- Fixed Speed and Variable Speed Models
- Air purity that meets the most stringent hygienic standards
- Outstanding reliability for demanding applications

- **Pressure range** 7.5 to 10.5 bar
- Volume flow 6.7 to 28.3 m³/min
- Motor power 90 to 160 kW



Main features and benefits

Best-in-Class Efficiency

With a 14% improvement in energy efficiency and a 9% improvement in delivered capacity, our new EnviroAire 90 - 160 Series offers unmatched performance and efficiency. Their design is



optimised with an analytics-modelled airflow and piping system, as well as water jacketed air end cooling and IE5, ultra-premium efficiency motor technology for VSD packages. You can also enjoy massive turndown with an integrated variable speed drive and condition-based variable speed fan blower control, helping to maximise your productivity and efficiency.

Market-Leading Reliability

Every design aspect incorporated into the oil-free EnviroAire 90 - 160 series has been optimised for ultimate reliability! From their UltraCoat™



mechanically bonded coating to reduce corrosion, smart no-loss drain, pneumatic blowdown and hydraulic inlet valve to their free-floating cooling system, V-Shield technology and the premium efficiency IE5 motors used in the TVS models, you can enjoy total peace of mind!

Flexible Design Options

Our compressors offer aircooled and water-cooled configurations, fixed and regulated speed, different pressure variants, extreme ambient temperature options, high dust filtration



and outdoor modifications for harsh environments and many more to best match your application.

Reducing Lifecycle Costs

Long-life consumables allow for reduced maintenance and lifecycle costs, but if maintenance is required, wear items such as filters and heat exchangers are all easily



accessible! Our EnviroAire 90 - 160 models also have other innovative components designed to reduce lifecycle costs, including hinged removable doors, which allow for safe and easy maintenance and package pre-filtration to keep dust and dirt out of your system.

Higher Rated Cooling Capacity

Our compressor systems are designed for operation at ambient conditions up to 46°C. This provides an additional cooling margin for trouble-free operation at higher temperatures, and again



contributes to the overall reliability and efficiency of the compressor package

"The design of these packages ensures that the service points are readily

Advanced Compressor Control -The New Governor 10 Controller

Our new advanced Governor 10 controller offers real-time information with an easy-to-use, customer-friendly controller interface. With built-in graphical trending, you can gain expert insights into your compressor's activity, allowing for optimum operation. Also, managing energy consumption has never been so easy, with its optional energy monitoring system and comprehensive energy dashboard, which displays consumption, cost and efficiency data. This way, the Governor 10 is able to quickly provide energy consumption data for analysis, as well as an easy-to-find summary for energy monitoring.




Reduce Maintenance Costs, Save Energy & Maximise Sustainability

Did you know that over 5 years, energy accounts for typically 80% of the total costs of a compressor? However, this high percentage also provides the opportunity for considerable savings. Our Governor 10 can help with this, but so can integrating a regulated speed compressor.

Why Regulated Speed Compressors?

At Gardner Denver, we fully integrate matched variable speed drives with the appropriate motors to maximise the efficiency and reliability of your systems. Our high-performance IE5 Hybrid Reluctance Motor (HRM) provides wide turndown, as well as the ability to turn off immediately at minimum speed, eliminating the need to continue running unloaded. Regulated speed compressors are known to provide the highest possible energy savings when delivering 100% oil-free, reliable, clean air.

Maintenance and Service Costs



Achieve up to 35% Savings over traditional fixed speed

Fixed speed compressors usually require a larger control band, while TVS compressors operate much closer to the target pressure. Every 1 bar (over required pressure costs an additional 7% in power!



Perfect motor - drive - airend design

EnviroAire-TVS Series features a high efficient Power Drive System that exceeds the class IES2 EN61800-9 requirements and assures high energy savings across broad flow range.

Long life ultra premium efficiency IE5 motors used on the TVS models contribute to world-class package efficiency levels to IEC 60034-30-2, at any load.

Wide regulation range

No cycles means substantial energy savings.

Why Connect 12 Plus compressed air management system?

Energy management is crucial for all compressed air users, as the highest cost factor of a compressor is the energy to run it.

Base load sequencing

Compressed air systems typically comprise of multiple compressors delivering air to a common distribution system. The addition of the optional base load sequencing module will allow central control of up to four compressors matching delivery to the plant demand.



Why a profitable investment?

- Harmonises the workload of up to 12 fixed or regulated speed compressors including downstream
- Eliminates energy waste by tightening the network pressure to the narrowest pressure band
- Equalises the running hours for economic servicing and increased uptime
- Optimum performance and monitoring
- Increased plant productivity



Compressed Air Heat Recovery - a profitable investment!

Why heat recovery

It is a thermodynamic fact that around 94% of the energy needed to run a compressor gets converted to heat. Without heat recovery, this heat is directly blown into the atmosphere.

The heat generated during compression is paid for as part of the process, then it creates additional costs as this heat needs to be removed by cooling fans. At the same time, most companies consume a lot of energy and money to generate hot process water, space heating or preheat water for steam generation.

Given that compressed air systems account for 10% of all electricity used in industry, and energy is the largest single lifecycle cost of a compressor, it makes sense to recover this heat, save energy and reduce costs.

Your benefits

- Significant savings in energy costs
- Extremely short payback time
- Low investment costs payback time typically less than 1 year
- Lower CO₂ emissions
- Turnkey solutions





Hot Water

Industrial Process

- Easy installation and operation
- Small ecological footprint
- High reliability
- No impact on the compressed air supply
- Available for all water-cooled T/TVS Series models



Heating



Steam Generation (pre-heating)

Air treatment and Condensate Management

Compressed air treatment

A modern production system and process demands increasing levels of air quality, and compressed air operators need to ensure that the downstream equipment also delivers on it 100%.



Filtration Removes free water, dirt particles and aerosols.



Adsorption dryer High-quality ISO Class 1, 2 and 3 for water- and oil-free compressed air used in the pharmaceutical, food and beverage, electronics and power generation industries.



Refrigeration dryer / Subfreeze Dried compressed air for ISO quality classes 3 and 4.



Condensate management

Electronic, timed and mechanical float traps used in all compressed air systems for the discharge of liquid condensate. Oil/ water separators for the efficient disposal of compressed air condensates.



Gas Generation Nitrogen generators in different construction. Customized solutions and aerosols.



Carbon Towers Eliminates oil vapor and hydrocarbons to 0.003mg/m³.



Pure

PUREAIR SERVICING & MAINTENANCE PROGRAMME

PureCare

Specifically developed to support our oil-free product range, the Gardner Denver PureCARE service programmes go beyond traditional service schemes to ensure uninterrupted quality compressed air supply coupled with optimum compressor performance, giving you peace of mind for your production and budgeting processes. PureCARE Service plans are delivered by factorytrained Gardner Denver technicians specifically to keep your oil-free compressed air system at peak performance, supported by the unrivalled quality and performance of Gardner Denver genuine parts. Each PureCare Service plan is tailored to your specific application and site circumstances, ensuring system reliability and productivity at optimum cost.

It all adds up to Peace of Mind

Lower Cost of Ownership

Service and Warranty Agreements provide the most cost-effective solutions based on your customised maintenance strategy.

Quality Results

Factory trained technicians allows you to focus on your core business, while they take care of your compressor system.

Increased Uptime

Service Agreements help decrease unplanned downtime and costly production interruptions.

Efficient Energy Use

Peak system efficiency is achieved through properly performed maintenance and inspection.

Peace of Mind

A Service agreement ensures an extended warranty. Depends on duration.







iConn Compressed Air Service 4.0

The T/TVS Series is equipped with iConn as standard. iConn is the smart, proactive real-time monitoring service that delivers in-depth and realtime knowledge on the system to our compressed air users.

- Advanced remote analysis
- Predictive evaluates historic data
- Maximises energy efficiency
- Optimises compressor performance
- Reduces downtime
- Vorks as an open standard
- Free on new compressors can be retrofitted
- Proactive maintenance
- ...why you cannot ignore iConn!



Gardner Denver genuine spare parts

Enjoy complete peace of mind.

Genuine Gardner Denver parts and lubricants ensure that compressed air plant reliability and efficiency is maintained at the highest standards. Gardner Denver spare parts and lubricants are distinguished by:

- Long service life, even under harshest conditions
- Minimum losses contributing to energy savings
- High reliability improves plant up-time
- Products manufactured with the strictest Quality Assurance Systems





Technical data

EnviroAire T/TVS 90 - 160kW Fixed Speed - Air and Water Cooled

	Cooling	Motor Rating	Nominal Pressure		Free Air Delivered (m³/min)			Dimensions L x W x H	Noise level dB(A)	Weight	
	Method	kW	7.5 bar g	8.5 bar g	10.5 bar g	7 bar g	8 bar g	10 bar g	mm	8 bar g	kg
EnviroAire T90	Air	90	•	•		17.4	16.7	14.6	2712 x 1825 x 2200	78	3441
	Water				•	17.6	16.7	14.9		75	3309
EnviroAire T110	Air	110	•	•	•	21.0	20.1	18.2	2712 x 1825 x 2200	78	3678
	Water					21.2	20.3	18.4		75	3546
EnviroAire T132	Air	132	•	•	•	24.7	23.7	21.8	2712 x 1825 x 2200	78	3932
	Water					24.9	23.9	22.0		75	3800
EnviroAire T160	Air	160		• •		28.1	28.0	25.9	2712 x 1825 x 2200	78	3934
	Water		•		•	28.3	28.0	26.1	2712 X 1025 X 2200	75	3802

Variable Speed - Air and Water Cooled

Gardner Denver model	Cooling Method	Motor Rating	Nominal Pressure	Free Air [(m³/		Dimensions L x W x H	Noise level dB(A)	Weight
		kW	bar g	min	max	mm	8 bar g	kg
	Air	90	10.7	7.0	17.2	2712 x 1825 x 2200	64 - 78	3297
EnviroAire TVS90 Water	Water	90		7.3	17.4		62 - 75	3165
EnviroAire TVS110	Air	110	10.7	7.0	19.7	2712 x 1825 x 2200	64 - 78	3297
	Water	110	10.7	7.3	19.9		62 - 75	3165
EnviroAire TVS132	Air	132	10.7	6.7	24.2	2712 x 1825 x 2200	64 - 78	3297
	Water	152		6.9	24.4		62 - 75	3165
EnviroAire TVS160	Air	100	10.7	6.7	26.7	2712 x 1825 x 2200	64 - 78	3297
	Water	160		6.9	26.9		62 - 75	3165

¹⁾ Data measured and stated in accordance with ISO 1217, Edition 4, Annex C and Annex E and the following conditions: Air Intake Pressure 1 bar a, Air Intake Temperature 20°C, Humidity 0 % (Dry).

 $^{2)}$ Measured in free field conditions in accordance with ISO 2151, tolerance ± 3dB (A).

Global Expertise

The GD rotary screw compressor range from 2.2 - 500 kW, available in both variable and fixed speed compression technologies, are designed to meet the highest requirements which the modern work environment and machine operators place on them.

The oil-free EnviroAire range from 15 – 355 kW provides high quality and energy efficient compressed air for use in a wide range of applications. The totally oil-free design eliminates the issue of contaminated air, reducing the risk and associated cost of product spoilage and rework.

A modern production system and process demands increasing levels of air quality. Our complete Air Treatment Range ensures the highest product quality and efficient operation.

Compressor systems are typically comprised of multiple compressors delivering air to a common header. The combined capacity of these machines is generally greater than the maximum site demand. To ensure the system is operated to the highest levels of efficiency, the GD Connect air management system is essential.

gdcompressors.eu@gardnerdenver.com www.gardnerdenver.com/gdproducts

For additional information please contact Gardner Denver or your local representative.

Specifications subject to change without notice.







