



SAFETY DOOR
INLOCK SWITCH

INPUT
POWER
ON LIGHT

ON/OFF SWITCH

HV POWER ON LIGHT

120V STANDARD 18/3 CORD
WITH 15 AMP 3-PRONG PLUG
(230V-1PH OPTIONAL)
3 FOOT LENGTH

POWER PACK DETAIL
SCALE 1 / 6

WATERWASH
MANIFOLDS,
(OPTIONAL)

6 X 1200 CFM UAPC
PRECIPITATOR CELLS

STANDARD
AIR FLOW

LOCATION OF WATERWASH
MANIFOLDS DEPENDS ON
DIRECTION OF AIR FLOW

1" ALUMINUM
MESH FILTER

POWER PACK
UNITS, MOUNTED

FOR ALL UNITS
ALLOW 3 FEET IN
FRONT OF UNIT
FOR CELL REMOVAL

DRAIN PORT, 2"NPTf
(OPTIONAL)

Ø3/4 INLET TUBES

LEGS (OPTIONAL)

COMPANY
CONFIDENTIAL

This drawing and all information herein is the property of Universal Air Products Corp. It is confidential and must not be made public or copied. It is loaned, subject to return upon demand. It is not to be used directly or indirectly in any way detrimental to the interests of UNIVERSAL AIR PRODUCTS.

NOTE: REMOTE POWER PACK PROVISIONS
AVAILABLE AS AN OPTION.

DRAWN KEF	6/26/2014	UNIVERSAL AIR & GAS PRODUCTS CORP. 1140 KINGWOOD AVE NORFOLK, VA 23502		
CHECKED		TITLE		
QA		C3-72H3: 7200 CFM COMMERCIAL 3 HIGH		
MFG		i3-72H3: 7200 CFM INDUSTRIAL 3 HIGH		
APPROVED		SIZE C	DWG NO i3-72H3	REV B
		SCALE 1/12	SHEET 1 OF 1	